


1. Cable Structure



Cable Diameter: 9.9MM Weight: 89KG/KM

CABLE STRUCTURE AND PARAMETERS:

Physical Parameters	Fiber Count	12
	Fiber Type	MM OM3 50/125µm
	Cable Outer Diameter(O.D.)	9.9mm
	Cable Weight	89KG/KM
	Outer Sheath Thickness	1.4mm
	Operating temperature range	-40°C to +60°C
	Storage / Transport temperature range	-50°C to +70°C
	Installation temperature range	-30°C to +50°C
Mechanical Parameters	Tensile Strength Long Term	800N
	Tensile Strength Short Term	1800N
	Crush Resistance	500N/100mm
	Bending Radius(Short Term)	20×O.D.
	Bending Radius(Long Term)	10×O.D.

Notes:

1. The nominal sheath thickness may vary by $\pm 0.2\text{mm}$.
2. The nominal outer diameter and weight may vary by $\pm 0.2\text{mm}$.

2. Color Code of Optical Fiber

Color Code of Fiber (Comply with IEC-793-2 and TIA/EIA-598-A Standard)

Fiber No.	1	2	3	4	5	6	7	8	9	10	11	12
Color	Blue	Orange	Green	Brown	Grey	White	Red	Black	Yellow	Violet	Pink	Aqua

Note) Color code may be changed upon customer's request.

3. Fiber Specifications

Fiber Type		G.652D	G.657A	OM1	OM2	OM3-150	OM3-300	OM4
		9/125μm	9/125μm	62.5/125μm	50/125μm	50/125μm	50/125μm	50/125μm
Attenuation (dB/km)	850nm	/	/	3.00	3.00	3.00	3.00	3.00
	1300nm	/	/	1.00	1.00	1.00	1.00	1.00
	1310nm	0.36	0.36	/	/	/	/	/
	1550nm	0.22	0.22	/	/	/	/	/
OFL	850nm	/	/	≥200	≥500	≥700	≥1000	≥3500
Bandwidth (MHZ·KM)	1300nm	/	/	≥500	≥500	≥500	≥500	≥500
Effective Modal Bandwidth (MHZ·KM)	850nm	/	/	/	/	≥950	≥2000	≥4700
Application Support	Gigabit Ethernet LX 1300nm	/	/	550	550	550	550	550
Distance on (m)	Gigabit Ethernet SX 850nm	/	/	275	550	750	800	880
	10 Gigabit Ethernet SX 850nm	/	/	33	82	150	300	550
	40G/100G Ethernet SX 850nm	/	/	/	/	/	100	150
Min. Bending Radius (mm)		30	10	30	30	30	30	30